



**RSC / RESIDENTIAL SECURITY CONTAINER**



**RSC / UL-Certified**



**ONE-HOUR Fire Factory Rating.**

Additional door seal Palusol™ Heat Activated expands 7X its size sealing the door during a fire.

- 1.5” thick construction body and 1.7” thick construction door
- 1/2” thick Ballistic Steel plate inside the door protecting the locks from frontal attack
- 1/4” thick Ballistic Steel plate inside the body protecting the bolts from side attack
- Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates (12 Ga steel body and 3/16 steel door and frame)
- Sophisticated Spring-Loaded Relocking System is activated and locked when attacked
- Large 1” diameter chrome plated steel bolts and force resistive handle
- High quality 30 mm diameter heavy duty hinges
- UL Certified Electronic



**WE CAN BUILD OTHER SIZES AS PER REQUEST**

Model Name	Interior (inches)			Exterior (inches)			Shelves	Volume	Weight	List Price
	Height	Width	Depth	Height	Width	* Depth	#	(ft. <sup>3</sup> )	(lbs.)	CAD
RSC 1317	13	17	14 1/2	16	20	20 1/8	1	1.85	355	
RSC 1713	17	13	14 1/2	20	16	20 1/8	1	1.85	355	
RSC 2113	21	13	14 1/2	24	16	20 1/8	1	2.29	380	
RSC 2517	25	17	14 1/2	28	20	20 1/8	1	3.57	490	
RSC 3218	32	18	14 1/2	35	21	20 1/8	2	4.84	616	
RSC 3717	37	17	14 1/2	40	20	20 1/8	2	5.28	690	
RSC 5621	56	21	21	59	24	26 3/4	4	14.30	1220	

\* Add 1-3/4" to outside depth for LG handle, dial and hinge projection.

**Reduced Depth version :**

RSC 1317-S	13	17	11 1/2	16	20	17 1/8	1	1.47	355	
RSC 1713-S	17	13	11 1/2	20	16	17 1/8	1	1.47	355	
RSC 2113-S	21	13	11 1/2	24	16	17 1/8	1	1.82	380	
RSC 2517-S	25	17	11 1/2	28	20	17 1/8	1	2.83	490	

\* Add 1-3/4" to outside depth for LG handle, dial and hinge projection.

**DONOVAN TL-15/UL CERTIFIED SERIES**



**TL15 / UL-Certified**

- UL TL-15 certified
- Large 1.5" diameter chrome plated steel bolts and force resistive handle
- 1" thick Ballistic Steel construction door and 1/2" thick Ballistic Steel construction body
- UL certified Group 2M manipulation resistant combination lock with spy proof dial.
- Sophisticated Glass Protected Relocking System is activated and locked when attacked
- High quality 30 mm diameter heavy duty hinges
- Door hinge side inter-locks with deadbolts preventing safe opening by hinge removal safes provide an alternative DSL UL TL15 certified composite safes where the weight is limited by the location where the safe is being installed.
- Custom sizes, interiors and other lock options available



**WE CAN BUILD OTHER SIZES AS PER REQUEST**

Model Name	Interior (inches)			Exterior (inches)			Shelves #	Volume (ft. <sup>3</sup> )	Weight (lbs.)	List Price CAD
	Height	Width	Depth	Height	Width	* Depth				
<b>DSL 1212</b>	12	12	10 1/4	13	13	15	1	0.86	206	
<b>DSL 2014</b>	20	14	14 3/4	21	15	19 5/8	1	2.47	380	
<b>Callisto 2120</b>	21	20	9 3/4	22	21	14 1/2	1	2.37	400	
<b>Callisto 2517</b>	25	17	15 1/4	26	18	20	1	3.75	520	
<b>Callisto 3219</b>	32	19	17 1/4	33	20	22	2	6.07	680	
<b>Callisto 3228</b>	32	28	21	33	29	25 3/4	2	10.89	902	
<b>Callisto 3519</b>	35	19	15 1/4	36	20	20	2	5.87	680	
<b>Callisto 3723</b>	37	23	17 1/4	38	24	22	2	8.50	895	
<b>Callisto 4520</b>	45	20	21 1/4	46	21	26	3	11.07	1030	
<b>Callisto 5520</b>	55	20	21 1/4	56	21	26	4	13.53	1230	

\* Add 1-3/4" to outside depth for LG handle, dial and hinge projection, or 3" for 5-Spoke handle, or 3 3/4" for Handlebar.  
Optional 3-way boltwork available for sizes 3219 and up.



**UL TL15 CERTIFIED SAFES / TITAN-SERIES**



**TL15 / UL-Certified**



**TWO-HOUR Fire Factory Rating.**

- Large 1.5" diameter chrome plated steel bolts and force resistive handle
- 2.5" thick construction body and 4" thick construction door
- UL certified Group 2M manipulation resistant combination lock with spy proof dial.
- 1/2" Ballistic Steel plate inside the door protecting the locks from frontal attack
- 1/4" thick Ballistic Steel plate inside the body protecting the bolts from side attack
- Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates (12Ga steel body, 1/4" thick steel door & frame, additional layer Ballistic steel barrier)
- Sophisticated Glass Protected Relocking System is activated and locked when attacked
- High quality 1.5" diameter heavy duty adjustable hinges.
- Stock safes come in grey splatter color, Inkas faceplate, one electronic lock and LG-handle; safes from TL15- 3219 and up supplied with 28-inch long handlebar.
- Options available described in detail on page 12.



**UL TL15 CERTIFIED SAFES / TITAN-SERIES**



**TL15 / UL-Certified**

WE CAN BUILD OTHER SIZES AS PER REQUEST

	Name	Interior (inches)			Exterior (inches)			Shelves	Volume	Weight	List Price
		Height	Width	Depth	Height	Width	* Depth	Q.ty	(ft. <sup>3</sup> )	(lbs.)	CAD
<b>SI</b>	TL15_1212	12	12	10	17	17	19 1/2	1	0.83	430	
	TL15_1918	19	18	12 1/2	24	23	22	1	2.47	720	
<b>SI</b>	TL15_2014	20	14	13 3/4	25	19	23 1/2	1	2.25	730	
<b>SI</b>	TL15_2517	25	17	13 3/4	30	22	23 1/2	1	3.40	890	
<b>SI</b>	TL15_3219	32	19	15 3/4	37	24	25 1/2	2	5.54	1180	
	TL15_3225	32	25	24	37	30	33 1/2	2	11.11	1560	
	TL15_3726	37	26	19 3/4	42	31	29 1/2	2	11.00	1940	
<b>SI</b>	TL15_4520	45	20	20 3/4	50	25	30 1/2	3	10.81	1720	
	TL15_4525	45	25	26 1/2	50	30	36	3	17.25	2190	
	TL15_4913	49	13	10	54	18	19 1/2	3	3.69	1220	
	** TL15_5035	50	35	27	55	40	36 1/2	4	27.34	3050	
	TL15_5117	51	17	12 1/2	56	22	22	4	6.27	1570	
	TL15_5517	55	17	12 1/2	60	22	22	4	6.76	1630	
	TL15_5520_13	55	20	13	60	25	22 1/2	4	8.28	1850	
<b>SI</b>	TL15_5520	55	20	20 3/4	60	25	30 1/2	4	13.21	2200	
	TL15_5524	55	24	20 3/4	60	29	30 1/2	4	15.85	2290	
	TL15_5738	57	38	20 3/4	62	43	30 1/2	4	26.00	3170	
<b>SI</b>	TL15_6523	65	23	20 3/4	70	28	30 1/2	5	17.95	2590	
<b>SI</b>	TL15_6532	65	32	20 3/4	70	37	30 1/2	5	24.98	3150	
	TL15_6730	67	30	19 3/4	72	35	29 1/2	5	23.00	3270	
	TL15_6738	67	38	19 3/4	72	43	29 1/2	5	29.10	3830	
<b>SI</b>	TL15_7437	74	37	20 3/4	79	42	30 1/2	5	32.88	3960	

**SI** - Stock item

\*Add 1-3/4" to outside depth for LG handle, dial and hinge projection, or 3" for 5-Spoke handle, or 3 3/4" for Handlebar.

\*\* Dimensions of this safe allows inside installation of safety deposit boxes.

Optional 3-way boltwork available for sizes 3219 and up.

UL TL30 CERTIFIED SAFES / NEPTUNE-SERIES



TL30 / UL-Certified



**TWO-HOUR Fire Factory Rating.**

- Large 1.5" diameter chrome plated steel bolts and force resistive handle
- 2.5" thick construction body and 4" thick construction door
- UL certified Group 2M manipulation resistant combination lock with spy proof dial.
- 1/2" Ballistic Steel plate inside the door protecting the locks from frontal attack
- 1/4" thick Ballistic Steel plate inside the body protecting the bolts from side attack
- Additional 1/4" thick full size Ballistic Steel plate barrier increasing protection from frontal attack
- Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates (12Ga steel body, 1/4" thick steel door & frame, additional layer Ballistic steel barrier)
- Sophisticated Glass Protected Relocking System is activated and locked when attacked
- High quality 1.5" diameter heavy duty adjustable hinges
- Stock safes come in grey splatter color, DSL faceplate, one electronic lock and LG-handle; safes from TL30- 3219 and up supplied with 28-inch long handlebar.
- Options available described in detail on page 12.





WE CAN BUILD OTHER SIZES AS PER REQUEST

	Name	Interior (inches)			Exterior (inches)			Shelves	Volume	Weight	List Price
		Height	Width	Depth	Height	Width	* Depth	Q.ty	(ft. <sup>3</sup> )	(lbs.)	CAD
<b>SI</b>	TL30_1212	12	12	10	17	17	19 1/2	1	0.83	438	
	TL30_1918	19	18	12 1/2	24	23	22	1	2.47	730	
<b>SI</b>	TL30_2014	20	14	13 3/4	25	19	23 1/2	1	2.25	740	
<b>SI</b>	TL30_2517	25	17	13 3/4	30	22	23 1/2	1	3.40	920	
<b>SI</b>	TL30_3219	32	19	15 3/4	37	24	25 1/2	2	5.54	1220	
	TL30_3225	32	25	24	37	30	33 1/2	2	11.11	1610	
	TL30_3726	37	26	19 3/4	42	31	29 1/2	2	11.00	2000	
<b>SI</b>	TL30_4520	45	20	20 3/4	50	25	30 1/2	3	10.81	1720	
	TL30_4525	45	25	26 1/2	50	30	36	3	17.25	2190	
	TL30_4913	49	13	10	54	18	19 1/2	3	3.69	1290	
	** TL30_5035	50	35	27	55	40	36 1/2	4	27.34	3150	
	TL30_5117	51	17	12 1/2	56	22	22	4	6.27	1660	
	TL30_5517	55	17	12 1/2	60	22	22	4	6.76	1690	
	TL30_5520_13	55	20	13	60	25	22 1/2	4	8.28	1920	
<b>SI</b>	TL30_5520	55	20	20 3/4	60	25	30 1/2	4	13.21	2280	
	TL30_5524	55	24	20 3/4	60	29	30 1/2	4	15.85	2400	
	TL30_5738	57	38	20 3/4	62	43	30 1/2	4	26.00	3290	
<b>SI</b>	TL30_6523	65	23	20 3/4	70	28	30 1/2	5	17.95	2700	
<b>SI</b>	TL30_6532	65	32	20 3/4	70	37	30 1/2	5	24.98	3290	
	TL30_6730	67	30	19 3/4	72	35	29 1/2	5	23.00	3400	
	TL30_6738	67	38	19 3/4	72	43	29 1/2	5	29.10	4000	
<b>SI</b>	TL30_7437	74	37	20 3/4	79	42	30 1/2	5	32.88	4150	

**SI** - Stock item

\*Add 1-3/4" to outside depth for LG handle, dial and hinge projection, or 3" for 5-Spoke handle, or 3 3/4" for Handlebar.

\*\* Dimensions of this safe allows inside installation of safety deposit boxes.

Optional 3-way boltwork available for sizes 3219 and up.



## UL TL30X6 CERTIFIED SAFES / SATURN-SERIES



TL30X6 / UL-Certified

**TWO-HOUR Fire Factory Rating.**

- Large 1.5" diameter chrome plated steel bolts and force resistive handle
- 4" thick construction body and 4" thick construction door
- UL certified Group 2M manipulation resistant combination lock with spy proof dial.
- 1/2" Ballistic Steel plate inside the door protecting the locks from frontal attack
- 1/4" thick Ballistic Steel plate inside the body protecting the bolts from side attack
- Additional 1/4" thick full size Ballistic Steel plate barrier increasing protection from ALL SIDES attack
- Full composite construction comprised of the highest quality barrier material enclosed within heavy steel plates (12Ga steel body, 1/4" thick steel door & frame, additional layer Ballistic steel barrier)
- Sophisticated Glass Protected Relocking System is activated and locked when attacked
- High quality 1.5" diameter heavy duty adjustable hinges
- Stock safes come in grey splatter color, DSL faceplate, one electronic lock and LG-handle; safes from TL30- 3219 and up supplied with 28-inch long handlebar.
- Options available described in detail on page 12.





**UL TL30X6 CERTIFIED SAFES / SATURN-SERIES**



**TL30X6 / UL-Certified**

WE CAN BUILD OTHER SIZES AS PER REQUEST

	Name	Interior (inches)			Exterior (inches)			Shelves	Volume	Weight	List Price
		Height	Width	Depth	Height	Width	* Depth	Q.ty	(ft. <sup>3</sup> )	(lbs.)	CAD
<b>SI</b>	TL30X6_2014	20	14	13 3/4	28	22	25	1	2.25	1212	
	TL30X6_2321	23	21	18	31	29	29 1/4	1	5.03	1830	
<b>SI</b>	TL30X6_2517	25	17	13 3/4	33	25	25	1	3.40	1540	
<b>SI</b>	TL30X6_3219	32	19	15 3/4	40	27	27	2	5.54	2040	
	TL30X6_3521	32	25	24	37	30	33 1/2	2	11.11	1560	
<b>SI</b>	TL30X6_4520	45	20	20 3/4	53	28	32	3	10.81	3020	
<b>SI</b>	TL30X6_4921	49	21	20 3/4	57	29	32	3	12.36	3200	
<b>SI</b>	TL30X6_5520	55	20	20 3/4	63	28	32	4	13.21	3420	
	TL30X6_6220	62	20	19 1/4	70	28	30 1/2	5	13.82	3620	
<b>SI</b>	TL30X6_6523	65	23	20 3/4	73	31	32	5	17.95	4315	
<b>SI</b>	TL30X6_6532	65	32	19 1/4	73	40	30 1/2	5	23.18	4850	
<b>SI</b>	TL30X6_7036	70	36	20 3/4	78	44	32	5	30.26	5600	

**SI** - Stock item

\*Add 1-3/4" to outside depth for LG handle, dial and hinge projection, or 3" for 5-Spoke handle, or 3 3/4" for Handlebar.

Optional 3-way boltwork available for sizes 3219 and up.

**VAULT DOORS**



**TWO-HOUR Fire Factory Rating.**

**SECURITY:** DSL Vault Doors offer security and fire protection similar or higher than TL15 certified safes.

**SAFETY:** DSL Vault Doors feature a sophisticated mechanism, yet simple to use “Panic room” style. It can be locked from inside the vault, denying others entrance or access of the vault. Simultaneously, the mechanism works as an emergency escape release in event of accident lock, loss of power or other emergencies.



**Front view**



**Back view**



**SPECIFICATIONS :**

- Bolts: 14 pcs, 1.5” diameter, three sides 8 pcs active retractable bolts, one side 6 pcs passive fixed bolts.
- Hinges: High quality 1.5” diameter heavy duty adjustable hinges. Doors have 180 degrees opening swing.
- Handle : 5 Spoke and hub, all chrome plated steel.
- Lock: UL Listed. Combination of the following: Electronic, Manual, Key.
- Relocker: Glass Protected, Dual internal system which activates when attacked.
- Composition: Ballistic steel, 1/4” steel faceplate, 3/16” and 12 GA steel layers, high performance aggregate.

**INSTALLATION:** DSL Vault Doors are designed to fit in pre-existing opening “sandwich” style adjustable to wall thickness. Out-Swing Vault doors can be anchored on all sides of the door frame as additional install option.

Model	Name	Dimensions and sizes (inches)			Wall Thickness Standard **	Range Frame Adjustment	Weight (lbs.) ***
		Thru opening	Rough opening*	Overall			
		Height x Width	Height x Width	Height x Width			
<b>Out-Swing</b>	<b>OSVD-35</b>	76 x 30 7/8	79 1/2	81 1/2	8” (inches)	7 3/4” — 8 3/4”	1090
			x	x	10” (inches)	9 3/4” — 10 3/4”	
<b>In-Swing</b>	<b>INVD-35</b>	74 5/8 x 29 1/4	35 1/2	39 1/2	12” (inches)	11 3/4” — 12 3/4”	1070

\*The actual size of the door for the rough opening is 79 1/4 x 35

\*\*We can build for different size wall thickness (standard sizes shown)

\*\*\*Weight shown for 8 inch wall

MORE CHOICES ARE COMING.  
( Call for details )